

# DATA SHEET

# TMI-Orion

---

# VACQ III



**Thermal profile mapping inside kilns during curing processes of bricks, tiles, ceramics.**

VACQ III is an autonomous data logger which enables the measurement of temperature inside kilns during ceramic, tile and brick curing processes. It has 8 or 16 thermocouple channels and is associated with industry-specific software Qlever Ceramics.

Qlever Ceramics software enables the visualization and mapping of thermocouple temperature inside kilns, and the matching of wagon position and temperature at corresponding locations. Positioning the instruments (burners, doors...) in the software helps anticipate possible failures.

## METROLOGY

Operating range	Measurement range	Resolution	Uncertainty of the internal reference channel*
Without thermal shield: from 0°C to 140°C  With thermal shield: from 0°C to 250°C during 60 hours. Other thermal profiles upon request.	Up to 1300°C	<±0.1 °C	+/- 0.1°C from 0°C to +140°C

Each logger can be calibrated and adjusted at the temperature points corresponding to the user's needs.

*\*The specified uncertainties correspond to two standard deviations. The uncertainties are calculated taking into account the various significant error sources, including the calibration probes, the equipment, the environmental conditions, the influence of the logger, repeatability, etc...*



## FUNCTIONS

- Start set up: immediate or delayed
- Time stamped measurement data
- Battery level alert with Qlever software

## TECHNICAL SPECIFICATIONS

<b>Material</b>	Logger body: 316L Stainless steel	
<b>Dimensions</b>	Body : D.67 mm x L.100 mm (without connector)	
<b>Number of channels</b>	8	Up to 8 connected thermocouple elements and up to 3 platinum sensors as reference channel for cold junction, and internal temperature of the box
	16	Up to 16 connected thermocouple elements and up to 6 platinum sensors as reference channel for cold junction, and internal temperature of the box
<b>Temperature sensor</b>	Thermocouples: type K (full scale 1300°C)	
<b>Memory capacity</b>	232,000 acquisitions divided by number of measurement channels	
<b>Acquisition rate</b>	Programmable: minimum 1 second, maximum 59 minutes and 59 seconds	
<b>Program duration</b>	Programmable: days, hours, minutes	
<b>Recording</b>	Programmable start: by date, hour, minute	
<b>Power</b>	User replaceable battery pack	
<b>Connectivity</b>	USB wired interface to the PC	
<b>External connection box (*)</b>	Number of channels	Adapted to the number of channels of the logger
	Connectors	Miniature, standard or universal (upon request)
	Material	304 Stainless Steel for the hose 316L Stainless steel for the box

(\*) We can study any customization of the box: connectors, format, flexible hose length.



**VACQ III body**



**VACQ III external connection box**



## AUTONOMY

The VACQ III is powered by a battery pack; its autonomy depends on environmental and operational conditions of the application (extreme temperatures, radio range, electromagnetic disturbances, data acquisition and transmission rate).

As a result of the variety of environments and operational conditions, TMI-Orion does not guaranty the battery lifetime and recommends that the user determine the battery lifetime according to his own process conditions and experience.

## SOFTWARE AND RELATED PRODUCTS

**VACQ III is used with the Qlever software platform.**

**Qlever software platform:** data acquisition, management and visualization of data from TMI-Orion data loggers. Qlever is installed on a PC and operates under Windows®

Vista/7/8/10. Data transmission and visualization are done after the industrial process.

- VACQ III product family includes VACQ III radio for real time monitoring.

## DELIVERABLES

**The VACQ III solution usually includes the following items:**

- VACQ III with batteries,
- The VACQ III external connection box,
- The logger calibration certificate,
- The logger configuration and calibration file.

**Optional, to be ordered separately:**

- One or more thermocouple probes with connectors,
- A USB wired interface for PC,
- Qlever software and User's guide,
- A transport case.

## SERVICES

**Maintenance:** TMI-Orion recommends annual preventative maintenance and calibration service for the replacement of o-rings, functional checking, calibration and adjustment.

**Accessories:** The battery packs, engineered by TMI-Orion, are replaceable by the user and are referenced in the documentation available on our website.

**Headquarters: TMI-Orion S.A.**  
Parc Bellegarde - Bâtiment A  
1, chemin de Borie  
34170 Castelnau-le-Lez - France  
T.: +33 (0)4 99 52 67 10 – F.: +33 (0)4 99 52 67 11

  
**www.tmi-orion.com**

**USA : TMI-USA, Inc.**  
11491 Sunset Hills Road, Suite 310  
Reston, VA 20190 - USA  
T : +1 703 668 0114 – F : +1 703 668 0118